

风冷式冷水机系列规格表(随机型) SPECIFICATIONS OF AIR-COOLED CHILLER SERIES (SMALL TYPE)

型号 Model	压缩机功率 Compressor capacity		名义制冷量 Refrigeration capacity			冰水流量 Ice water flow rate	风扇型式 Fan type	冰水管径 Ice water pipe size	泵浦功率 Pump capacity	泵浦流量 Pump flow rate	泵浦扬程 Pump head	冷凝器型式 Condenser type	蒸发器型式 Evaporator type	水箱容量 Tank capacity	外形尺寸 Dimension	重量 Weight
	HP	KW	KW	Kcal/hr	Btu/hr	M3/hr		PT	KW	L/min	M		PG*	L	L*W*H(mm)	KG
SGPG-04M	0.40	0.30	1.48	1276	5062	0.26	轴流侧吹	3/4"	0.37	68	14	翅片式	盘管式	30	610*490*920	80
SGPG-05M	0.50	0.38	1.86	1597	6338	0.32	轴流侧吹	3/4"	0.37	68	14	翅片式	盘管式	30	610*490*920	82
SGPG-10M	1.00	0.75	2.06	1773	7035	0.35	轴流侧吹	3/4"	0.37	68	14	翅片式	盘管式	35	610*490*920	90
SGPG-15M	1.50	1.13	3.40	2924	11604	0.58	轴流上吹	3/4"	0.37	68	14	翅片式	盘管式	35	660*530*1000	95
SGPG-20M	2.00	1.50	4.42	3801	15085	0.76	轴流上吹	3/4"	0.37	68	14	翅片式	盘管式	40	660*530*1000	110
SGPG-25M	2.50	1.88	5.62	4835	19189	0.97	轴流上吹	3/4"	0.37	68	14	翅片式	盘管式	40	660*530*1000	120

备注 Remarks: 1. 以上电源规格为: 1P-220V-50Hz, 允许电压波动±10%, 允许相间电压差±2%, 冷媒为R22;

The above power supply is 3P-380V-50Hz, permission voltage hunting ±10%, permission interaction voltage difference ±2%, and refrigerant is R22.

2. 以上制冷能力条件为: 冰水入口温度12℃, 出口温度7℃, 环境温度35℃;

The above nominal capacity is based on chilling water inlet temperature at 12℃, outlet temperature at 7℃, ambient temperature at 35℃.

3. 规格如有变更, 以实机为准, 恕不另行通知。

If specification is changed, then the actual model shall govern.